



Fast Break Degreaser Technical Data

Description

Environmentally friendly, biodegradable quick break degreaser with superior degreasing properties. Formulated for use with oily water separators. Enviro Fast Break Degreaser's formulation consists of natural organic materials that satisfy the most stringent solvent performance and ecological toxicity criteria and is completely phosphate free.

Enviro Fast Break Degreaser is water based with a high flash point making it safe to handle and store

Environmental Considerations

The superior quick break ability and efficiency of Enviro Fast Break Degreaser make it the degreaser of choice in environmentally sensitive areas. Primary degradation for the Enviro surfactant is essentially complete in 3 days. Enviro Fast Break Degreaser contains no phosphates and does not cause eutrophication in the water system. Enviro Fast Break Degreaser has no known hazardous decomposition products.

Quick break properties

Enviro Fast Break Degreaser uses solvents that are considered "Not Water Endangering" (West German Classification). These solvents along with the naturally derived surfactants clean oil and grease off surfaces by emulsification. When the degreaser is rinsed off the oil the "break" process commences and within a few minutes most of the oil has broken and risen to the top of the solution where it can be removed. The water remaining can be discharged to the sewer.

Multiple Applications

Use Enviro Fast Break Degreaser for cleaning and degreasing mining equipment and machinery, industrial equipment, earthmoving equipment, washing parts, engine cleaning, ship's engines and bilges, concrete floors, service station forecourts, kitchen and washroom floors and through high pressure washers. Product is sea water compatible for use in marine applications.

Directions

1. Spray on or brush
Apply liberally to surfaces that are to be cleaned. Allow to stand for 5 minutes and then rinse off with water.
2. Tank Application.

Soak for at least 15 minutes. Then remove, drain and rinse off with water.
Mild steel tank construction acceptable.

3. Parts washer.

Set up as per manufacturer's instructions.

4. Concrete cleaning.

Apply to concrete and allow 2/3 minutes to soak in. Scrub with yard broom and then rinse off with water.

Recommended dilutions

Heavy soils Use undiluted

Medium soils Dilute 1:4

Light soils Dilute 1:10

Pressure washers Dilute 1:100

Safety

Rubber gloves and safety glasses recommended.

Before using read the label and the Material Safety Data sheet for Hazard Warnings and First Aid Instructions.

Packaging

5 litre plastic container

22.5 litre plastic container

200 litre drum

2000 litre bulky bin

Issued: 1st September 2002